



#126 NON-FIBERED ALUMINUM ROOF COATING

TROPICAL ROOFING PRODUCTS' #126 NON-FIBERED ALUMINUM ROOF COATING is extremely brilliant, durable and designed to withstand extreme weather conditions. TROPICAL ROOFING PRODUCTS' unique formulations make this dependable product stand out above the rest. Our use of paint grade aluminum paste (as used in bridges & water towers) gives a much higher quality and brighter leafing finish. A resin formulation is also added during the mixing process to change the characteristics of the asphalt itself to give a harder, shinier finish. #126 reflects over 70% of the sun's rays, allowing drastic reductions in interior temperatures, while protecting the underlayment. #126 can be used on roofs of all types, storage tanks, masonry surfaces and structural steel. #126 is also an excellent rust and corrosion resistant coating for all types of metal surfaces. #126 exceeds the parameters of ASTM D-2824, Type I.

PREPARATION: Surface must be clean and dry, free of moisture both on and beneath the surface. Sweep roof thoroughly to remove as much dust, dirt, and debris as possible. Use wire brush to remove rust and scale from metal. After careful inspection of entire roof, repair all holes, cracks, tears or breaks with glass reinforcing fabric and #701 Flashing Cement. **ALLOW REPAIRS TO CURE 30 DAYS BEFORE COATING.**

APPLICATION: Apply a thin, single coat of #126 over the entire surface with a soft bristle brush, paint roller or heavy-duty spray equipment. Avoid over-application. **DO NOT HEAT CONTAINER. DO NOT THIN.** Stir thoroughly before and during application.

COVERAGE: Apply at the rate of 1 to 1½ gallons per 100 square feet.

PRECAUTIONS: Do not heat container or store at temperatures greater than 120°F. **DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 24 HOURS.** Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. This coating is not recommended over PVC sheet roofing, rubber, gravel, shingles of any kind, or old roofs that are too dry and brittle.

DO NOT USE IF RAIN IS IMMINENT - COATING MUST BE DRY BEFORE EXPOSURE TO WATER
CAUTION - Apply according to ASTM D3805, allow roof to cure thoroughly before coating.

CLEANUP: Clean tools with mineral spirits or paint thinner.

MAXIMUM V.O.C = 500 G/L
CONSISTENCY — Thick Black Liquid
WEIGHT — 7.8 lbs. per gal +/- .2
FLASH POINT (T.C.C.) — 107°F+
DRYING TIME — Average: 2-5 hrs. to touch

**ASTM
D-2824
Type 1**

www.tropicalroofingproducts.com



FLORIDA
1904 SW 31st Ave.
Hallandale, FL 33009
fax: 954.963.2033
toll-free: 800.432.2855

CALIFORNIA
14435 Macaw Street
La Mirada, CA 90638
fax: 714.670.1605
toll-free: 877.827.2622

TEXAS
1225 Brai Drive, P.O. Box 5335
Port Arthur, TX 77640
fax: 409.727.4647
toll-free: 866.727.0091





#126 NON-FIBERED ALUMINUM ROOF COATING

CAUTION! COMBUSTIBLE!

Contains petroleum distillate. Keep away from heat and flame. USE ONLY WITH ADEQUATE VENTILATION! Avoid contact with skin and breathing of vapor. CLOSE AIR INTAKES on roof until solvents dissipate. KEEP OUT OF REACH OF CHILDREN. Close container after each use. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. DO NOT TAKE INTERNALLY! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY! Contains volatile solvents that might contaminate potable water.

For a totally unsurpassed aluminum paint ask for Tropical's #106 with 25% more aluminum pigment per gallon.

www.tropicalroofingproducts.com



FLORIDA
1904 SW 31st Ave.
Hallandale, FL 33009
fax: 954.963.2033
toll-free: 800.432.2855

CALIFORNIA
14435 Macaw Street
La Mirada, CA 90638
fax: 714.670.1605
toll-free: 877.827.2622

TEXAS
1225 Brai Drive, P.O. Box 5335
Port Arthur, TX 77640
fax: 409.727.4647
toll-free: 866.727.0091

